




Product Dimensions, Standards and Weights

DIN 1474 / ISO 8741 Technical Specifications

Metric DIN 1474 Grooved Pins 1/2 Reverse Taper Groove



Dimensions of Metric DIN 1474 Grooved Pins 1/2 Reverse Taper Groove

d1	Nominal		1.5	2	2.5	3	4	5	6	8	10	12	16	20	25
	tolerance		h9								h11				
a	=		0.2	0.25	0.3	0.4	0.5	0.63	0.8	1	1.2	1.6	2	2.5	3
The smallest cutting force two sections			1.6	2.84	4.4	6.4	11.3	17.6	25.4	45.2	70.4	101.8	181	283	444
kN															
l			Groove diameter												
Nominal	min.	max.	0.05 0		±0.05							±0.1			
8	7.75	8.25	1.6	2.1	2.6	3.1									
10	9.75	10.25	1.6	2.1	2.6	3.1	4.15	5.15							
12	11.5	12.5	1.63	2.1	2.6	3.1	4.15	5.15	6.15						
14	13.5	14.5	1.63	2.1	2.65	3.15	4.2	5.2	6.15	8.2					
16	15.5	16.5	1.63	2.1	2.65	3.15	4.2	5.2	6.15	8.2					
18	17.5	18.5	1.63	2.15	2.65	3.2	4.2	5.2	6.25	8.2	10.2				
20	19.5	20.5	1.63	2.15	2.65	3.2	4.2	5.2	6.25	8.2	10.2				
22	21.5	22.5		2.15	2.7	3.2	4.25	5.25	6.25	8.25	10.2				
24	23.5	24.5		2.15	2.7	3.2	4.25	5.25	6.25	8.25	10.2				
26	25.5	26.5		2.15	2.7	3.25	4.25	5.25	6.3	8.3	10.3	12.25	16.25	20.25	25.25
28	27.5	28.5		2.15	2.7	3.25	4.25	5.25	6.3	8.3	10.3	12.25	16.25	20.25	25.25
30	29.5	30.5		2.15	2.7	3.25	4.25	5.25	6.3	8.3	10.3	12.25	16.25	20.25	25.25
32	31.5	32.5				3.25	4.25	5.25	6.3	8.35	10.3	12.3	16.3	20.25	25.25



UNIQUE FASTENERS

Precision Fasteners, Built to Last
175/6 Sar Building, Sp Road, Bangalore, 560002

+91-8660813791

uniquefasteners.in

INFO@UNIQUEFASTENERS.IN



d1	Nominal		1.5	2	2.5	3	4	5	6	8	10	12	16	20	25
	tolerance		h9								h11				
a	=		0.2	0.25	0.3	0.4	0.5	0.63	0.8	1	1.2	1.6	2	2.5	3
The smallest cutting force two sections kN			1.6	2.84	4.4	6.4	11.3	17.6	25.4	45.2	70.4	101.8	181	283	444
l			Groove diameter												
Nominal	min.	max.	0.05 0		±0.05							±0.1			
35	34.5	35.5				3.25	4.25	5.25	6.3	8.35	10.3	12.3	16.3	20.25	25.25
40	39.5	40.5				3.25	4.3	5.3	6.3	8.35	10.4	12.3	16.3	20.3	25.3
45	44.5	45.5					4.3	5.3	6.35	8.35	10.4	12.4	16.4	20.3	25.3
50	49.5	50.5					4.3	5.3	6.35	8.4	10.4	12.4	16.4	20.4	25.4
55	54.25	55.75					4.3	5.3	6.35	8.4	10.45	12.4	16.4	20.4	25.4
60	59.25	60.75					4.3	5.3	6.35	8.4	10.45	12.5	16.5	20.5	25.5
65	64.25	65.75							6.35	8.4	10.45	12.5	16.5	20.5	25.5
70	69.25	70.75							6.35	8.4	10.45	12.5	16.5	20.5	25.5
75	74.25	75.75							6.35	8.4	10.45	12.5	16.5	20.5	25.5
80	79.25	80.75							6.35	8.35	10.45	12.5	16.5	20.5	25.5
85	84.25	85.75							8.35	10.45	12.5	16.5	20.5	25.5	25.5
90	89.25	90.75							8.35	10.45	12.5	16.5	20.5	25.5	25.5
95	94.25	95.75							8.35	10.4	12.5	16.5	20.5	25.5	25.5
100	99.25	100.75							8.35	10.4	12.5	16.5	20.5	25.5	25.5
120	119.25	120.75								10.4	12.45	16.45	20.5	25.5	25.5
140	139.25	140.75								10.4	12.45	16.45	20.45	25.45	25.45
160	159.25	160.75								10.4	12.45	16.45	20.45	25.45	25.45
180	179.25	180.75									12.45	16.45	20.45	25.45	25.45
200	199.25	200.75									12.45	16.45	20.45	25.45	25.45



UNIQUE FASTENERS

Precision Fasteners, Built to Last
175/6 Sar Building, Sp Road, Bangalore, 560002



+91-8660813791



uniquefasteners.in



INFO@UNIQUEFASTENERS.IN



Metric DIN 1474 grooved pins 1/2 reverse taper groove (ISO 8741) have three longitudinal tapered grooves that expand the pin's diameter. When inserted into the straight hole the expanded diameter is pressed back to the nominal diameter. As the pin tries to expand to the larger diameter the force against the hole's wall tightens the fit. This creates the holding power against shock and vibration. Unique Fasteners offers one of the most complete ranges of metric pins and other inch and metric industrial fasteners for immediate delivery from stock. The following sizes of metric DIN 1474 grooved pins 1/2 reverse taper groove are available for immediate shipping from stock: Diameters ranging from M2 to M8 up to 60mm long in 303 stainless steel.

DIN (**D**eutsches **I**nstitut für **N**ormung - German Institute for Standardization) standards are issued for a variety of components including industrial fasteners as Metric DIN 1474 grooved pins 1/2 reverse taper groove. The DIN standards remain common in Germany, Europe and globally even though the transition to ISO standards is taking place. DIN standards continue to be used for parts which do not have ISO equivalents or for which there is no need for standardization. In this case the ISO equivalency is ISO 8741