GSTIN-29ADMPC3767H1Z9



UNIQUE FASTENERS

Precision Fasteners, Built to Last 175/6 Sar Building, Sp Road, Bangalore, 560002








Product Dimensions and Weights

DIN 6885 Technical Specifications

Metric DIN 6885 Parallel Keys High Type "A"



Dimensions of Metric DIN 6885 Parallel Keys High Type "A"

| b | h9 | 4 | 5 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 25 |
|-----------|-----------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|
| h | h11 | 4 | 5 | 6 | 7 | 8 | 8 | 9 | 10 | 11 | 12 | 14 | 14 |
| for shaft | over | 10 | 12 | 17 | 22 | 30 | 38 | 44 | 50 | 58 | 65 | 75 | 85 |
| diameters | to | 12 | 17 | 22 | 30 | 38 | 44 | 50 | 58 | 65 | 75 | 85 | 95 |
| | | | | | | | | | | | | | |
| | | | | | | | | | | | | | |
| b | h9 | 28 | 32 | 36 | 40 | 45 | 50 | 56 | 63 | 70 | 80 | 90 | 100 |
| b h | h9 h11 | 28 16 | 32 18 | 36 20 | 40 22 | 45 25 | 50 28 | 56 32 | 63 32 | 70 36 | 80 40 | 90 45 | 100 50 |
| | _ | _ | _ | | _ | _ | | | | _ | | | |

Metric DIN 6885 Parallel Key High Type "A" (aka feather keys) is a component used to connect machine assemblies to a shaft in order to prevent relative rotation between the two parts. For a key to function, the shaft and rotating machine element must have a keyway and a keyseat, which is a slot and pocket in which the key fits. Unique Fasteners offers the following sizes for immediate delivery from stock: Diameters ranging from M5 to M14 and up to 90mm long and available in 316Ti stainless steel.