
GSTIN-29ADMPC3767H1Z9



UNIQUE FASTENERS

Precision Fasteners, Built to Last 175/6 Sar Building, Sp Road, Bangalore, 560002










Product Dimensions and Weights

DIN 908 Technical Specifications

Metric DIN 908 Hexagon Socket Screw Plug with Collar



D1	D2	S	С	ı	Length approx	T min
M10 x 1.0	14	5	3	8	11	5
M12 x 1.5	17	6	3	12	15	7
M14 x 1.5	19	6	3	12	15	7
M16 x 1.5	21	8	3	12	15	7.5
M18 x 1.5	23	8	4	12	16	7.5
M20 x 1.5	25	10	4	14	18	7.5
M22 x 1.5	27	10	4	14	18	7.5
M24 x 1.5	29	12	4	14	18	7.5
M26 x 1.5	31	12	4	16	20	9
M27 x 2.0	32	12	4	16	20	9
M30 x 1.5	36	17	4	16	20	9
M33 x 2.0	39	17	5	16	21	9
M36 x 1.5	42	19	5	16	21	10.5
M38 x 1.5	44	19	5	16	21	10.5
M42 x 1.5	49	22	5	16	21	10.5
M45 x 1.5	52	22	5	16	21	10.5
M48 x 1.5	55	24	5	16	21	10.5
M52 x 1.5	60	24	5	16	21	10.5
M56 x 2.0	64	32	5	20	25	14
M64 x 2.0	72	32	5	20	25	14

All measurements are in mm

GSTIN-29ADMPC3767H1Z9



UNIQUE FASTENERS

Precision Fasteners, Built to Last 175/6 Sar Building, Sp Road, Bangalore, 560002







Metric DIN 908 Type A hexagon socket screw plugs with collar/flange and cylindrical / straight thread are threaded plugs with a hexagon socket drive (allen drive) at the collar end and cylindrical (parallel/straight) pipe thread along most of the length of the other end. The collar provides a larger bearing surface to seat flush in a preformed hole or on the surface of the mating substrate when fully tightened. Sealing gaskets are available in aluminum (DIN 908 Type AA) and in copper (DIN 908 Type AC). These are typically used to seal cylindrically threaded holes in pipes and fittings carrying air, gases or fluids under pressure. Often additional sealing coating such as thread seal tape ("teflon tape"), a liquid pipe sealant applied to the threads, or preapplied sealant is necessary for a perfect seal. Metric DIN 908 Type A hexagon socket screw plugs with collar/flange and cylindrical / straight thread are available in brass, steel as well as stainless steel A2 and A4. Unique Fasteners offers one of the most complete ranges of metric screw plugs and other inch and metric industrial fasteners for immediate delivery from stock. The following sizes of metric DIN 908 hexagon socket screw plugs with collar and cylindrical thread are available for immediate shipping from stock: Diameters ranging from M10 to M48 in brass, steel and stainless steel A2 and A4.

DIN (**D**eutsches **I**nstitut für **N**ormung - German Institute for Standardization) standards are issued for a variety of components including industrial fasteners as metric DIN 908 hexagon socket screw plugs with collar and cylindrical thread. The DIN standards remain common in Germany. Europe and globally even though the transition to ISO standards is taking place. DIN standards continue to be used for parts which do not have ISO equivalents or for which there is no need for standardization like DIN 908 hexagon socket screw plugs with collar and cylindrical thread.